

#### **DS-PDC15-EG2-WB**

DS-PDC15-EG2-WE is a two-way wireless detector featuring a solid curtain coverage up to 15m length by 3.6m height, it suitable for perimeter protection by setting up detection "curtain" walls or windows

- Long range with narrow angle detection
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission



# Specification

Passive Infrared				
15 m				
6.3°				
18				
0.3 ~ 2 m/s				
None				
6500lux				
Support				
Support				
Support				
Support				
Support				
Front, Rear				
Support				
Support				
Support				
Power Up Enrolling				
Blue(Alarm)				
Tri-X Wireless				
Two-Way RF Wireless				
433 MHz				
AES-128 Encryption				
1.2 Km				
Support				
Power up, Remote ID, QR Code				
Enrolling Method Power up, Remote ID, QR Code  Electrical Characteristics				
5 years in work status (being triggered 20 times per day)				
Battery Powered				
CR123A × 1				
3 V				
-10 °C to 55 °C (14 °F to 131 °F)				
-20 °C to 60 °C (-4 °F to 140 °F)				
10% to 90%				
65.5 mm × 103 mm × 48.5 mm				
128 g				
128 g 2.4 to 3.6 m				



Application Scenario	Indoor
Bracket	Optional Wall & Ceiling Accessory

### Available Model

DS-PDC15-EG2-WB

# Accessory

## Optional

DS-PDB-IN-Wall bracket	DS-PDB-IN-Ceiling bracket	DS-PDP-IN-CR123A
Internal wall mounted	Internal ceiling mounted	Indoor Detector
bracket	bracket	Battery
0		CR123A 3.0V —



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ







