

# DS-PS1-I-WB Wireless Internal Sounder

The wireless internal sounder, supporting 433 MHz wireless communication, Tri-X wireless protocol, multiple enrollment methods, two-way wireless communication, multiple alarm sounds, and strobe light indication, is used for instant alarm alerting.

# HIKVISION

## **Key Features**

- 433 MHz two-way wireless communication
- Configurable arming/disarming prompt sound and LED indicator
- 3 years battery life span (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 90 to 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

### **Available Model**

• DS-PS1-I-WB (433MHz)





Model		DS-PS1-I-WB
RF	Frequency	433 MHz
	Modulation	2GFSK
	Method	Two-way communication
	RF encryption	AES-128
	RF distance	900m (open area)
Electrical & battery	Power	Battery
	Consumption	Static consumption: 30 to 40uA
	Battery life span	3 CR123A, 3 years in work status
		(triggered every two weeks and
		alerting 90 s for each triggering)
Interface and component	Power switch	Supported
	Tamper switch	Supported, Front and rear
		tamper-proof
	Indicator	Indicator: Red/Green/Amber
		Strobe light: Red/Blue
	Buzzer	Decibel: 90 to 110 dB
General	Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Operation humidity	10% to 90% (no condensing)
	Color	White
	Material	PC+ABS
	Dimension (W × H × D)	88× 88 × 32 mm (3.46" ×3.46" × 1.26")
	Weight	169.5 g (6.0 oz)
	Installation	Wall mounting
Approvals	FCC	Supported
	CE/CB	Supported
	RCM	Supported
	Rohs/Reach/WEEE	Supported





# **HIKVISION**°

### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com



© Hikvision Digital Technology Co., Ltd. 2019 | Data subject to change without notice |