

DH-SD1A404XB-GNR-W

4M 4x Starlight IR WizSense Network PTZ Camera



Wiz Sense

- 1/2.8" 4Megapixel STARVIS™ CMOS
- Starlight technology
- Max. 25/30fps@4MP
- 4x optical zoom
- Face Detection, People Counting, Perimeter Protection
- IR distance up to 15m
- WIFI (support 2.4G & 5G)
- SMD Plus
- IP66, IK08



Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

System Overview

Dahua WizSense PTZ camera adopts advanced CNN deep learning algorithms to support perimeter protection with high accuracy. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

Functions

People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30 °C to +60 °C (-22 °F to +140 °F) with 95% humidity. Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

Protection

The camera allows for $\pm 15\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR optimizes both the bright and dark areas of a scene at the same time to provide usable video.

H.265+

H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

Technical Specification

Camera

Image Sensor	1/2.8" STARVIS™ CMOS
Pixel	4MP
Max. Resolution	2560 (H) × 1440 (V)
ROM	4GB
RAM	1GB
Electronic Shutter Speed	1/1 s–1/30000 s
Scanning System	Progressive
Min. Illumination	Color: 0.005Lux@F1.8 B/W: 0.0005Lux@F1.8 0Lux (IR light on)
Illumination Distance	15 m (49.21 ft)
Illuminator On/Off Control	Zoom Prio/Manual/SmartIR
Illuminator Number	3

Lens

Focal Length	2.8 mm–12 mm			
Max. Aperture	F1.8–F2.7			
Field of View	H: 31.6°–96.9° V: 17.8°–51.4° D: 36.4°–116.2°			
Optical Zoom	4x			
Focus Control	Auto/Semi-Auto/Manual			
Close Focus Distance	0.2 m–0.5 m (0.66 ft– 1.64 ft)			
Iris Control	Auto			
DORI Distance	Detect	Observe	Recognize	Identify
	147 m (482.28 ft)	58.8 m (192.91 ft)	29.4 m (96.46 ft)	14.7 m (48.23 ft)

PTZ

Pan/Tilt Range	Pan: 0°–355° Tilt: 5°–90°
Manual Control Speed	Pan: 0.1°/s–70°/s Tilt: 0.1°/s–30°/s
Preset Speed	Pan: 80°/s Tilt: 40°/s
Presets	300
Tour	8 (up to 32 presets per tour)
Speed Adjustment	Support
Power-off Memory	Support
Idle Motion	Preset/Tour

General Intelligence

Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
IVS	Object Abandoned/Missing

Artificial Intelligence

People Counting	Count people entering and exiting the area (crossing people counting); count people staying in the area (in-area people counting); display and export reports by day, week and month.
Perimeter Protection	Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, etc.
SMD Plus	Support
Face Detection	Support

Video

Compression	H.265; H.264BaselineProfile; H.264MainProfile; H.264HighProfile; MJPEG(Sub Stream); H.265+; H.264+
Streaming Capability	3 streams
Resolution	4M (2560 x 1440); 3M (2048 x 1536); 1080P (1920 x 1080); 1.3M (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480); CIF (352 x 288/352 x 240)
Frame Rate	Main stream: 4M/3M (1–25/30fps), 1080P/1.3M/720P (1–25/30fps) Sub stream 1: D1/CIF (1–25/30fps) Sub stream 2: 720P (1–25/30fps), D1/CIF (1–25/30fps)
Bit Rate Control	Variable Bit Rate/Constant Bit Rate
Bit Rate	H.264/H.265/MJPEG: 3 kbps–20480 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Support
WDR	120 dB
HLC	Support
White Balance	Auto/Indoor/Outdoor/Track/Manual/Sodium lamp/Natural light/Street lamp
Gain Control	Auto/Manual
Noise Reduction	2D/3D
Motion Detection	Support
Region of Interest (RoI)	Support
Electronic Image Stabilization	Support
Electronic Defog	Support
Digital Zoom	16x
Flip	0°/180°
Privacy Masking	Up to 24 areas, and up to 8 areas in the same view

Audio

Compression	G.711a; G.711Mu; G.726; AAC; MPEG2-Layer2; G.722.1; G.729; G.723
-------------	--

Network

Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	Support
Protocol	IPv4; IPv6; HTTP; HTTPS; 802.1x; Qos; FTP; SMTP; UPnP; SNMPv1/v2c/v3(MIB-2); DNS; DDNS; NTP; RTSP; RTP; TCP; UDP; IGMP; ICMP; DHCP; PPPoE; ARP; RTCP
Interoperability	ONVIF Profile S&G&T; CGI

Streaming Method	Unicast/Multicast
User/Host	20
Storage	FTP; Micro SD card (256G); P2P
Browser	IE; Chrome; Firefox; Safari (no version restriction)
Management Software	SmartPSS; DSS
Mobile Phone	iOS/Android

Certification

Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014 UL:UL62368-1+CAN/CSA C22.2, No. 62368-1
----------------	---

Port

Audio Input	1(Line in; bare wire or built in Mic)
Audio Output	1

Power

Power Supply	DC12V/1.5A±15%
Power Consumption	3W 8.5W (IR on)

Environment

Operating Temperature	-30°C to +60°C (-22°F to 140°F)
Operating Humidity	≤95%
Protection	IK08; IP66; TVS 6000V lightning proof; surge protection

Structure

Casing	Metal
Dimensions	Φ128.0 mm × 65.4 mm (5.04" × 2.57")
Net Weight	0.485 kg (1.06 lb)
Gross Weight	0.7 kg (1.54 lb)

Ordering Information

Type	Model	Description
4MP WizSense PTZ Camera	DH-SD1A404XB-GNR-W	4M 4x Starlight IR WizSense Network PTZ Camera, WIFI, PAL
	DH-SD1A404XBN-GNR-W	4M 4x Starlight IR WizSense Network PTZ Camera, WIFI, NTSC
	SD1A404XB-GNR-W	4M 4x Starlight IR WizSense Network PTZ Camera, WIFI, PAL
	SD1A404XBN-GNR-W	4M 4x Starlight IR WizSense Network PTZ Camera, WIFI, NTSC
Accessories	PFA107	Mount Adapter
	PFB305W	Wall Mount Bracket
	DH-PFA120	Junction Box
	DH-PFA140	Power Box
	DH-PFA151	Corner Mount Bracket
	PFB220C	Ceiling Mount Bracket
	DH-PFA150	Pole Mount Bracket
	DC12V/1.5A	Power Adapter

Accessories

Optional:



Ceiling Mount (1)	Wall Mount	Ceiling Mount (2)
	PFA107+PFB305W 	PFA107+PFB220C
Pole Mount (1)	Pole Mount (2)	Corner Mount
PFA107+PFB305W+PFA150 	PFA107+PFB220C+PFA150 	PFA107+PFB305W+PFA151

Dimensions (mm[inch])

