



# RG 2.5GBASE Series Optical Modules



Scan QR Code  
For More Enquiry

[sales@rxtx.com.au](mailto:sales@rxtx.com.au)

+61 45 22 45 222



[www.rxtx.com.au](http://www.rxtx.com.au)

## Product Pictures



## Product Overview

variety of high-density and low-power 2.5G optical modules. They are applicable to data center and campus networks, enabling cost-effective, efficient, and high-speed interconnection among switches, routers, servers, and network interface controllers (NICs).

### 2.5G-SFP-LX03-SM1310-BIDI-I Module

The 2.5G-SFP-LX03-SM1310-BIDI-I is aligned to IEEE 2.5GBASE-LX optical specifications and supports a link length of up to 3 kilometers over a single mode fiber (SMF) with a BIDI LC connector. It adopts the SFP form factor and operates at a wavelength of 1310 nm. The transceiver conforms to SFF-8431, SFF-8472, and RoHS standards.

### 2.5G-SFP-LX03-SM1550-BIDI-I Module

The 2.5G-SFP-LX03-SM1550-BIDI-I is aligned to IEEE 2.5GBASE-LX optical specifications and supports a link length of up to 3 kilometers over an SMF with a BIDI LC connector. It adopts the SFP form factor and operates at a wavelength of 1550 nm. The transceiver conforms to SFF-8431, SFF-8472, and RoHS standards.

# Product Features

- Hot swapping, allowing for simplified maintenance
- High reliability and low power consumption, allowing for prolonged service life
- Compliance with RoHS and FDA standards

# Product Specifications

## Optical Module Specifications

Model	2.5G-SFP-LX03-SM1310-BIDI-I	2.5G-SFP-LX03-SM1550-BIDI-I
Data rate	3.125 Gbps	
Form factor	SFP	
Connector type	BIDI LC	
Cable type	SMF	
Fiber end face finish type	Ultra Physical Contact (UPC)	
Transmitter type	FB	DFB
Receiver type	PIN	
Reach	3 km (9,842.52 ft.)	
Bit error ratio (BER)	1.00E-12	
Data diagnosis-capable (DDM/DOM)	Yes	
Power consumption	≤ 1 W	
Transmitter Optical Parameters		
Wavelength	1310 nm TX 1550 nm RX	1550 nm TX 1310 nm RX
Max. transmit power (AVG)	-3 dBm	
Min. transmit power (AVG)	-9 dBm	

Model	2.5G-SFP-LX03-SM1310-BIDI-I	2.5G-SFP-LX03-SM1550-BIDI-I
Min. extinction ratio	≥ 6.5 dB	
Receiver Optical Parameters		
Receive sensitivity (OMA)	< -16 dBm	
Overload optical power (AVG)	-3 dBm	
Environment and Reliability		
Operating temperature	-40°C to +85°C (-40°F to +185°F)	
Operating humidity	10% RH to 90% RH	
Storage temperature	-40°C to +85°C (-40°F to +185°F)	
Storage humidity	10% RH to 90% RH	
Dimensions and Weight		
Dimensions (W x D x H)	56.5 mm x 13.5 mm x 8.5 mm (2.22 in. x 0.51 in. x 0.33 in.)	
Weight	35 g (0.08 lbs.)	

## Ordering Information

Model	Description
2.5G-SFP-LX03-SM1310-BIDI-I	2.5G LX module, SFP form factor, BIDI LC, 3 km (9,842.52 ft.) over SMF
2.5G-SFP-LX03-SM1550-BIDI-I	2.5G LX module, SFP form factor, BIDI LC, 3 km (9,842.52 ft.) over SMF



Ruijie Networks Co., Ltd.

For further information, please visit our website <https://www.ruijienetworks.com>

All rights are reserved by Ruijie Networks Co., Ltd. Ruijie reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.