



DESCRIPTION

The GT-MKB-N is a video guard station for the GT Series multi-tenant video intercom system. It can be surface mounted to the wall on a 3-gang electrical box, or may be desk mounted using the included desk stand. The GT-MKB-N features a keypad for calling both tenant and entrance stations. There is also a handset for private communication. There are up and down buttons to search for a tenant name via the directory, and a door release button to selectively open the entrance where communication is established.

The GT-MKB-N has two calling modes, standard (via tenant station) and emergency (via GFK-PS). When a standard call is placed, a normal call tone is heard and the name and number of the caller are displayed on screen. When an emergency call is placed, an urgent call tone is heard and the "EMERGENCY" screen with the name and number of the caller is displayed on screen. A standard call is reset by hanging up the GT-MKB-N handset and an emergency call must be reset at the tenant location.

The GT-MKB-N can be programmed manually, programmed via a PC using the supplied USB cable, or programmed via an Android™ device using NFC. A standard GT Series system will support 2 GT-MKB-Ns while an expanded system will support 4 GT-MKB-Ns.

The system has one talk path. When the system is occupied, a busy tone will be heard if another call is attempted.


FEATURES

- Handset or hands-free open voice for quick communication
- Standard and internal emergency calls
- Communicate with entrance and tenant stations
- Visitor screening with video
- Caller ID with call back
- Input for an optional video door station (JO-DV)
- Service button
- External signaling
- Surface mount to wall with 3-gang box or desk mount using included stand
- Program with PC or Android™ app

GT-MKB-N

Video Guard Station

FEATURE CALL-OUT



FEATURE CALL-OUT DEFINITIONS

- [1] Handset
- [2] Speaker
- [3] Color LCD screen
- [4] Status LED (orange)
- [5] NFC reader
- [6] Option button
- [7] Microphone
- [8] Off button
- [9] Adjust button
- [10] Zoom/Wide button
- [11] Up/Down/Left/Right button
- [12] Talk button
- [13] Door release button
- [14] Monitor button
- [15] Keypad (0 to 9, *, #)
- [16] Multi-function buttons
 - Light
 - Video call (transfer)
 - List
 - Settings

GT-MKB-N with desk stand



SPECIFICATIONS

- Power Source:** 24V DC, PS-2420UL per 2 units
- Call:** Varying ring tones from entrance, tenant, or door stations
- Communication:** Hands-free, VOX, or PTT
Handset (full duplex) or PTT
- Screen:** 3.5" TFT color LCD
- Capacity:** Max. 2 GT-MKB-Ns in a standard system
Max. 4 GT-MKB-Ns in an expanded system
- Wiring:** 2-conductor, PE insulation, common bus
Aiphone #872002, 2-cond. PE insulated, non-shielded, 20AWG
- Wiring Distance:**
 - (GT-BC audio): 980' with 20AWG
 - (GT-VBC video): 490' with 18AWG
- Talk Path:** Single channel with privacy
- Operating Temp:** 32~104°F (0~40°C)
- Dimensions (HxWxD):** 6-3/8" x 9-13/16" x 1-1/2"
(162 x 250 x 37.5 mm)
- Weight (with stand):** 2.64 lbs (1.2kg)