

# 8-Port 10/100Mbps + 3-Port Gigabit Desktop Switch with 8-Port PoE+

MODEL: TL-SL1311MP Datasheet



## Highlights

- With eight PoE+ ports, transfers data and power on one single cable
- Working with IEEE 802.3af/at compliant PDs, expands your network
- Supports PoE power up to 30 W for each PoE port
- Supports PoE power up to 124 W\* for all PoE ports
- Up to 250 m data and power transmission under Extend Mode\*\* specially designed for surveillance system
- Isolation Mode allows one-click client traffic separation for higher security and performance
- With PoE Auto Recovery, the switch will automatically reboot your dropped or unresponsive PoE-powered devices connected to port 1-8
- Requires no configuration and installation
- Fanless Design

## Overview

TL-SL1311MP is an unmanaged switch with 8 10/100 Mbps ports, 2 1000 Mbps ports, and 1 SFP slot that requires no configuration, and provides 8 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

## Power Over Ethernet

8 10/100 Mbps Auto-Negotiation RJ45 ports (port 1 to port 8) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af/at compliant Powered Devices (PDs).

## Overload Arrangement

TL-SL1311MP has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is  $\geq 124 \text{ W}^*$ , a priority will be arranged among the PoE ports, then the system will cut off the power of the lowest-priority port.

## Intelligent Power Management

Priority (port 1 > port 2 > port 3 > ... > port 8): This function will help protect the system when the system power is overloaded. For example, port 1, 2, 3 and 5 is using 25 W respectively (maximum power per port is 30 W); the system power is 100 W in total. If there is an additional PD inserted to port 4 with 30 W, and then the system will cut off the power of port 5 because of the overloaded power, this means port 1, 2, 3 will use 25 W respectively and port 4 will use 30 W, no power will be supplied to port 5.

## Highlight Performance

- Up to 250 m PoE power supply and data transmission under Extend Mode\*\*.
- Isolation Mode easily divides traffic for port 1–8 to avoid snooping and tampering, which improves LAN security and performance.
- With PoE Auto Recovery, the switch will constantly detect the data transmission with PoE-powered devices (PD). When the switch finds that a PD stops sending data packets to the switch for a long period, the switch will reboot it automatically.

## Easy to Use

TL-SL1311MP is easy to install and use. It requires no configuration and installation. With desktop and wall mountable design, outstanding performance and quality, the TP-Link 8-Port 10/100Mbps + 3-Port Gigabit Desktop Switch with 8-Port PoE+TL-SL1311MP is a great selection for expanding your network.

# Specifications

## Hardware Features & Performance

Product Picture	
Model	TL-SL1311MP
Standards	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.3z
Network Ports	8* 10/100 Mbps RJ45 ports with PoE+ (port 1 to port 8) 2* 1000 Mbps RJ45 ports 1* 1000 Mbps SFP Slot
Network Media (Cable)	10Base-T: UTP category 3, 4, 5 cable (maximum 100 m) EIA/TIA-568 100 Ω STP (maximum 100 m) 100Base-TX: UTP category 5, 5e cable (maximum 100 m) EIA/TIA-568 100 Ω STP (maximum 100 m)
PoE	PoE Standard: IEEE 802.3af, IEEE 802.3at PoE Port 1–8, up to 30 W per port PoE Power Budget 124 W*
Auto-Negotiation	YES
Auto MDI/MDIX	YES
PoE Power on RJ45	Power+: pin 3 & pin 6 Power -: pin 1 & pin 2
Max Power Consumption	5.95 W (220 V/50 Hz no PD connected) 140.92 W (220 V/50 Hz with 124 W* PD connected)
Max Heat Dissipation	20.29 BTU/h (220 V/50 Hz no PD connected) 480.54 BTU/h (220 V/50 Hz with 124 W* PD connected)
Forwarding Mode	Store and Forward
Switch Capacity	7.6 Gbps
MAC Address Table	2k, Auto-learning, Auto-aging
Extend Mode	YES
Isolation Mode	YES
PoE Auto Recovery	YES
Flow Control	YES
Fanless	YES
Dimensions	8.2 x 4.9 x 1.0 in (209 x 126 x 26mm)
Certification	CE, FCC

### Note:

\* PoE budget calculations are based on laboratory testing. Actual PoE power budget is not guaranteed and will vary as a result of client limitations and environmental factors.

\*\* The speed of the ports which are under extend mode will be downgraded to 10Mbps. Actual transmission distance may vary from the quality of the cables.